

S Couplers

Series **KK** General purpose type

- Effective area: **3.8 to 82 mm²**
(Series KK2) (Series KK6)
- Weight: **6.1 to 87.7 g**
(Series KK2) (Series KK6)
- With sleeve lock mechanism (Except for KK2)



Series **KKH** With shock absorption cover

- Use of rubber sleeve cover and shock resistant cover ring enables Series KKH to absorb impact energy when dropped.
- Effective area is equivalent to that of Series KK.



Series **KKA** Stainless steel type

- Body material: SUS304
- Seal material: FKM
- Non-greased specification



Series **KK13** Manufactured by Rectus



Variations

Series KK General purpose type

P.2~10

Male thread type

Series	Port size					
	M5	R1/8	R1/4	R3/8	R1/2	R3/4
KK2	●	●				
KK3		●	●	●		
KK4		●	●	●	●	
KK6				●	●	●

Female thread type

Series	Port size				
	M5	Rc1/8	Rc1/4	Rc3/8	Rc1/2
KK2	●				
KK3		●	●	●	
KK4			●	●	
KK6				●	●

Nut fitting type (for fiber reinforced urethane hose)

Series	Applicable hose I.D./O.D. mm					
	5/8	6/9	6.5/10	8/12	8.5/12.5	11/16
KK3	●	●	●			
KK4	●	●	●	●	●	
KK6				●	●	●

One-touch fitting type (Straight-Elbow-Bulkhead)

Series	Applicable tubing O.D. mm					
	ø3.2	ø4	ø6	ø8	ø10	ø12
KK2	●	●	●			
KK3		●	●	●	●	
KK4			●	●	●	●
KK6						●

Types marked with "●" are newly added variations.



Series KK3-4-6



Series KK2

Series KKH With shock absorption cover

P.11~13

Male thread type

Series	Port size			
	R1/8	R1/4	R3/8	R1/2
KKH3	●	●	●	
KKH4	●	●	●	●

Female thread type

Series	Port size		
	Rc1/8	Rc1/4	Rc3/8
KKH3	●	●	●
KKH4	●	●	●

Nut fitting type (for fiber reinforced urethane hose)

Series	Applicable hose I.D./O.D. mm				
	5/8	6/9	6.5/10	8/12	8.5/12.5
KKH3	●	●	●		
KKH4	●	●	●	●	●

Types marked with "●" are newly added variations.



Series KKA Stainless steel type

P.14~20

Male thread type

Series	Port size				
	R1/8	R1/4	R3/8	R1/2	R3/4
KKA3	●	●	●		
KKA4		●	●	●	
KKA6			●	●	●

Female thread type

Series	Port size				
	Rc1/8	Rc1/4	Rc3/8	Rc1/2	Rc3/4
KKA3	●	●	●		
KKA4		●	●	●	
KKA6			●	●	●



Series KK13 Manufactured by Rectus

P.21~25

Male thread type

Series	Port size			
	R1/8	R1/4	R3/8	R1/2
KK13	●	●	●	●

Female thread type

Series	Port size			
	Rc1/4	Rc3/8	Rc1/2	G1/4
KK13	●	●	●	●

Barb fitting type

Series	Applicable hose I.D.			
	1/4"	1/4"	3/8"	1/2"
KK13	●	●	●	●

Plug nut fitting type (for fiber reinforced urethane hose)

Series	Applicable hose I.D./O.D. mm					
	5/8	6/9	6.5/10	8/12	8.5/12.5	11/16
KK13	●	●	●	●	●	●





S Couplers

Series KK

M5 size (Series KK2) is newly added.

General purpose type

Employs a unique connection method


A slim body design and large effective area are achieved with a construction that does not use steel balls and therefore does not restrict the flow path.

No spring located in the flow path

Loss of effective area is minimized because there is no valve spring to block the flow path.


Check valve end configuration facilitates rectifying effect

Allows smooth flow of fluids.



Light weight

Together with a reduction of the body size, pressing parts and resin parts are used to achieve an overall weight reduction.



Series	Plug no.	Socket no.	Effective area mm ² Note 1)	Body O.D. mm	Weight g Note 2)
Series KK2	KK2P-M5M	KK2S-M5M	3.8	ø10.0	6.1
Series KK3	KK3P-01MS	KK3S-01MS	20	ø18.2	18.9
Series KK4	KK4P-02MS	KK4S-02MS	39	ø25.4	41.3
Series KK6	KK6P-04MS	KK6S-04MS	82	ø31.2	87.7

Note 1) Values when plug and socket are connected.

Note 2) Values for socket only.

One-touch fitting type standardized

Three types from ø4 to ø16 added to series.




Flow is possible from the plug side or socket side.

Fluids: Air and Water


One-touch connection

Simple connection with one hand simplifies work.



Low leakage seal construction

Reliable sealing is achieved by surface contact.



Sleeve lock mechanism

Prevents accidents caused by unexpected separation.

Note) Except for M5 type (Series KK2).



Series KK

Plug (P)

Male thread type

	Body size	Port size	Part no.
	M5	M5 x 0.8	KK2P-M5M
		R 1/8	-01MS
	1/8	R 1/8	KK3P-01MS
		R 1/4	-02MS
		R 3/8	-03MS
	1/4	R 1/8	KK4P-01MS
		R 1/4	-02MS
		R 3/8	-03MS
	1/2	R 1/2	-04MS
		R 3/8	KK6P-03MS
		R 1/2	-04MS
		R 3/4	-06MS

Female thread type

	Body size	Port size	Part no.
	M5	M5 x 0.8	KK2P-M5F
		Rc 1/8	KK3P-01F
	1/8	Rc 1/4	-02F
		Rc 3/8	-03F
	1/4	Rc 1/4	KK4P-02F
		Rc 3/8	-03F
		Rc 3/8	KK6P-03F
	1/2	Rc 1/2	-04F
		Rc 1/2	-04F
		Rc 1/2	-04F

Nut fitting type (for fiber reinforced urethane hose)

	Body size	Applicable hose I.D./O.D. mm	Part no.
	1/8	5/8	KK3P-50N
		6/9	-60N
		6.5/10	-65N
	1/4	5/8	KK4P-50N
		6/9	-60N
		6.5/10	-65N
		8/12	-80N
		8.5/12.5	-85N
	1/2	8/12	KK6P-80N
		8.5/12.5	-85N
		11/16	-110N

Straight type with One-touch fitting

	Body size	Applicable tubing O.D. mm	Part no.
	M5	3.2	KK2P-23H
		4	-04H
		6	-06H
	1/8	4	KK3P-04H
		6	-06H
		8	-08H
	1/4	10	-10H
		6	KK4P-06H
		8	-08H
	1/2	10	-10H
		12	-12H
		12	KK6P-12H
		16	-16H

Elbow type with One-touch fitting

	Body size	Applicable tubing O.D. mm	Part no.
	M5	3.2	KK2P-23L
		4	-04L
		6	-06L
	1/8	4	KK3P-04L
		6	-06L
		8	-08L
	1/4	10	-10L
		6	KK4P-06L
		8	-08L
	1/2	10	-10L
		12	-12L
		12	KK6P-12L
		16	-16L

Bulkhead type with One-touch fitting

	Body size	Applicable tubing O.D. mm	Part no.
	M5	3.2	KK2P-23E
		4	-04E
		6	-06E
	1/8	4	KK3P-04E
		6	-06E
		8	-08E
	1/4	10	-10E
		6	KK4P-06E
		8	-08E
	1/2	10	-10E
		12	-12E
		12	KK6P-12E
		16	-16E

Socket (S)

Male thread type

	Body size	Port size	Part no.
	M5	M5 x 0.8	KK2S-M5M
		R 1/8	-01MS
	1/8	R 1/8	KK3S-01MS
		R 1/4	-02MS
		R 3/8	-03MS
	1/4	R 1/8	KK4S-01MS
		R 1/4	-02MS
		R 3/8	-03MS
	1/2	R 1/2	-04MS
		R 3/8	KK6S-03MS
		R 1/2	-04MS
		R 3/4	-06MS

Female thread type

	Body size	Port size	Part no.
	M5	M5 x 0.8	KK2S-M5F
		Rc 1/8	KK3S-01F
	1/8	Rc 1/4	-02F
		Rc 3/8	-03F
	1/4	Rc 1/4	KK4S-02F
		Rc 3/8	-03F
		Rc 3/8	KK6S-03F
	1/2	Rc 1/2	-04F
		Rc 1/2	-04F
		Rc 1/2	-04F

Nut fitting type (for fiber reinforced urethane hose)

	Body size	Applicable hose I.D./O.D. mm	Part no.
	1/8	5/8	KK3S-50N
		6/9	-60N
		6.5/10	-65N
	1/4	5/8	KK4S-50N
		6/9	-60N
		6.5/10	-65N
		8/12	-80N
		8.5/12.5	-85N
	1/2	8/12	KK6S-80N
		8.5/12.5	-85N
		11/16	-110N

Straight type with One-touch fitting

	Body size	Applicable tubing O.D. mm	Part no.
	M5	3.2	KK2S-23H
		4	-04H
		6	-06H
	1/8	4	KK3S-04H
		6	-06H
		8	-08H
	1/4	10	-10H
		6	KK4S-06H
		8	-08H
	1/2	10	-10H
		12	-12H
		12	KK6S-12H
		16	-16H

Elbow type with One-touch fitting

	Body size	Applicable tubing O.D. mm	Part no.
	M5	3.2	KK2S-23L
		4	-04L
		6	-06L
	1/8	4	KK3S-04L
		6	-06L
		8	-08L
	1/4	10	-10L
		6	KK4S-06L
		8	-08L
	1/2	10	-10L
		12	-12L
		12	KK6S-12L
		16	-16L

Bulkhead type with One-touch fitting

	Body size	Applicable tubing O.D. mm	Part no.
	M5	3.2	KK2S-23E
		4	-04E
		6	-06E
	1/8	4	KK3S-04E
		6	-06E
		8	-08E
	1/4	10	-10E
		6	KK4S-06E
		8	-08E
	1/2	10	-10E
		12	-12E
		12	KK6S-12E
		16	-16E

S Couplers

Series *KK*


General purpose type



Series KK2

Series KK3, 4, 6

JIS symbols



Specifications

Fluid	Air, Water (standard industrial water)
Operating pressure range ^{Note)}	KK2: -100kPa to 1.0MPa KK3: -90kPa to 1.0MPa KK4-6: 0 to 1.0MPa
Proof pressure	1.5MPa
Ambient and fluid temperature	Air: -5 to 60°C Water: 5 to 40°C (with no freezing)
Plating, Sealant	Electroless nickel plated (copper-free application), With male thread sealant

Note) Do not use the S couplers with a leak tester or for vacuum retention because they are not guaranteed for zero leakage.

Performance

Plug and socket connection	One-touch connection and release
Check valve	Socket: Built-in check valve (standard)
Sleeve lock mechanism ^{Note)}	Manual locking type (standard)

Note) Series KK2 is not provided with lock mechanism.

Effective Area

Body size	Plug	Socket	Effective area mm ²
M5	KK2P-M5M	KK2S-M5M	3.8
1/8	KK3P-01MS	KK3S-01MS	20
1/4	KK4P-02MS	KK4S-02MS	39
1/2	KK6P-04MS	KK6S-04MS	82

How to Order

KK 4 S-02 M S

- Body size**

2	M5
3	1/8
4	1/4
6	1/2
- Socket/Plug designation**

S	Socket
P	Plug
- Connection type**

Symbol	Type
M	Male thread
F	Female thread
N	With nut fitting
H	Straight with One-touch fitting
L	Elbow with One-touch fitting
E	Bulkhead with One-touch fitting
- Piping port size variation**

Male/Female thread type	
Symbol	Thread size
M5	M5 x 0.8
01	R, Rc 1/8
02	R, Rc 1/4
03	R, Rc 3/8
04	R, Rc 1/2
06	R, Rc 3/4

One-touch fitting type	
Symbol	Applicable tubing O.D. mm
23	ø3.2
04	ø4
06	ø6
08	ø8
10	ø10
12	ø12
16	ø16


Nut fitting type	
Symbol	Applicable hose I.D./O.D. mm
50	5/8
60	6/9
65	6.5/10
80	8/12
85	8.5/12.5
110	11/16

• With sealant (male thread)

Flow Characteristics


Air (0 to 1 MPa)

KK2




Water (0 to 0.4 MPa)


KK2



KK3,4,6




KK3,4,6



Construction

KK2



Plug


No.	Description	Material	Note
1	Stem	Brass	Electroless nickel plated
2	Gasket	Stainless steel, NBR	

Socket

No.	Description	Material	Note
1	Spacer	PBT	
2	Chuck	PBT	
3	Sleeve	Brass	Electroless nickel plated
4	Collar	Brass	Electroless nickel plated
5	Sleeve spring	Stainless steel	
6	Plug O-ring	NBR	
7	Valve seat	PBT	
8	Valve spring	Stainless steel	
9	Valve seat O-ring	NBR	
10	Valve O-ring	FKM	
11	Valve	PBT	
12	Socket body	Brass	Electro nickel plated
13	Gasket	Stainless steel, NBR	

KK3,4,6

<With One-touch fitting >



Plug

No.	Description	Material	Note
1	Stem	Brass	Electroless nickel plated
14	Cassette	—	
15	Seal	NBR	

Socket

No.	Description	Material	Note
1	Body	Brass	Electroless nickel plated
2	Valve	PBT	
3	Valve seat	PBT	
4	Collar	PBT	
5	Spacer	PBT	
6	Lock ring	PBT	
7	Sleeve	Cold rolled carbon steel sheet	Electroless nickel plated
8	Chuck	Stainless steel	
9	Valve O-ring	FKM	
10	Valve seat O-ring	NBR	
11	Plug O-ring	NBR	
12	Valve spring	Stainless steel	
13	Sleeve spring	Stainless steel	
14	Cassette	—	
15	Seal	NBR	
16	Collar 2	Stainless steel	

Series KK

Dimensions/Plug (P)

Male thread type

KK2





KK3/4/6



Body size	Model	T Connection port size	H Width across flats	L1	L2	A*	Min. bore size	Effective area mm ²	Weight g
M5	KK2P-M5M	M5 x 0.8	7	18.8	12.3	15.8	2.5	4.4	2.6
	-01MS	R 1/8		23.2		19.2	3.4	8.1	3.0
	KK3P-01MS	R 1/8	10	30.4	18.4	26.4	6.0	22.6	8.4
1/8	-02MS	R 1/4	14	33.4		27.4			14.2
	-03MS	R 3/8	17	36.9	19.9	30.4			28.1
1/4	KK4P-01MS	R 1/8	14	37.0	25.2	33.0	9.0	50.9	17.0
	-02MS	R 1/4		40.2		34.2			20.2
	-03MS	R 3/8	17	42.2		35.7			32.5
	-04MS	R 1/2	22	46.2		38.2			57.4
1/2	KK6P-03MS	R 3/8	19	48.0	31.0	41.5	11.0	76.0	44.7
	-04MS	R 1/2	22	52.0		44.0	13.0	106.2	53.7
	-06MS	R 3/4	27	55.0		45.5			94.4

* Reference dimension for R threads after installation.


(mm)



Female thread type




Body size	Model	T Connection port size	H Width across flats	L1	L2	Min. bore size	Effective area mm²	Weight g
M5	KK2P-M5F	M5 x 0.8	8	17.6	12.3	3.4	8.1	2.6
1/8	KK3P-01F	Rc 1/8	14	28.3	18.4	6.0	22.6	10.4
	-02F	Rc 1/4	17	35.0	19.0			20.8
	-03F	Rc 3/8	19	36.8				23.2
1/4	KK4P-02F	Rc 1/4	17	37.2	25.2	9.0	50.9	23.9
	-03F	Rc 3/8	19	39.8				24.6
1/2	KK6P-03F	Rc 3/8	19	43.3	31.0	13.0	106.2	28.6
	-04F	Rc 1/2	24	50.2				43.9



Nut fitting type (for fiber reinforced urethane hose)



Body size	Model	Applicable hose I.D./O.D. mm	H1 Width across flats	H2 Width across flats	L1	L2	M	Min. bore size	Effective area mm²	Weight g	
1/8	KK3P-50N	5/8	14	14	36.1	18.4	13.7	4.5	12.7	21.4	
	-60N	6/9	17	39.9	16.5		5.4	18.3	38.8		
	-65N	6.5/10					5.9	21.9	35.9		
1/4	KK4P-50N	5/8	17	14	43.9	25.2	13.7	4.5	12.7	34.7	
	-60N	6/9		17	46.7		16.5	5.4	18.3	48.4	
	-65N	6.5/10						5.9	21.9	45.1	
	-80N	8/12	47.6		17.4		7.4	34.4	53.2		
	-85N	8.5/12.5					7.8	38.2	55.6		
1/2	KK6P-80N	8/12	19	19		53.4	31.0	7.4	34.4	60.5	
	-85N	8.5/12.5			7.8			38.2	62.8		
	-110N	11/16			24			24	57.2	20.1	10.2




Straight type with One-touch fitting

(mm)



Body size	Model	Applicable tubing O.D. mm	øD1	øD2	L1	L2	M	Min. bore size	Effective area mm ²		Weight g
									Urethane tubing	Nylon tubing	
M5	KK2P-23H	ø3.2	10.0	7.0	20.5	12.3	12.7	2.5	3.7	4.4	3.3
	-04H	ø4		8.0				3.4	8.1	8.1	3.4
	-06H	ø6		10.0	23.5			13.5			4.0
1/8	KK3P-04H	ø4	12.0	10.0	35.4	18.4	16.0	3.2	3.9	5.6	7.9
	-06H	ø6	14.0	12.0			17.0	4.7	10.1	12.8	9.1
	-08H	ø8	16.0	14.0			18.5	6.0	15.7	22.6	13.2
	-10H	ø10	19.0	17.0			21.0		22.6		17.6
1/4	KK4P-06H	ø6	14.0	12.0	46.2	25.2	17.0	4.7	10.1	12.8	22.3
	-08H	ø8	16.0	14.0			18.5	6.2	19.8	22.6	23.0
	-10H	ø10	19.0	17.0			21.0	7.7	27.6	35.3	27.1
	-12H	ø12	21.0	19.0			22.0	9.0	40.2	50.9	30.0
1/2	KK6P-12H	ø12	21.0	19.0	56.1	31.0	22.0	9.2	41.2		44.4
	-16H	ø16	26.0	25.7			25.0	13.0	—	106.2	50.7




Elbow type with One-touch fitting

(mm)



Body size	Model	Applicable tubing O.D. mm	øD1	øD2	L1	L2	L3	M	Min. bore size	Effective area mm ²		Weight g
										Urethane tubing	Nylon tubing	
M5	KK2P-23L	ø3.2	10.0	9.3	24.0	12.3	16.5	12.7	2.5	3.6	4.3	5.8
	-04L	ø4		11.6	25.1		16.6	13.5	3.4	7.8	7.8	6.4
	-06L	ø6		10.4	31.6		18.0	16.0	3.0	3.7	5.3	7.2
1/8	KK3P-04L	ø4	12.0	10.4	31.6	18.4	20.0	17.0	4.5	10.1	11.4	8.0
	-06L	ø6		12.8	32.8		23.0	18.5	6.0	15.0	16.8	9.7
	-08L	ø8		15.2	34.0		26.5	21.0		18.0	18.5	23.0
	-10L	ø10		17.0	36.0		20.0	17.0	4.5	10.1	11.4	19.6
1/4	KK4P-06L	ø6	14.0	12.8	40.2	25.2	23.0	18.5	6.0	17.5	19.8	21.3
	-08L	ø8	17.0	15.2	41.4		26.5	21.0	7.5	24.7	27.5	25.7
	-10L	ø10		18.5	42.8		28.5	22.0	9.0	29.0	29.6	28.0
	-12L	ø12		20.9	44.0		34.0	25.0	13.0	—	58.7	48.7
1/2	KK6P-12L	ø12	19.0	18.5	49.9	31.0	28.5	22.0	9.0	38.1	39.7	40.3
	-16L	ø16	21.0	20.5	53.5		34.0	25.0	13.0	—	58.7	48.7




Bulkhead type with One-touch fitting

(mm)



Body size	Model	Applicable tubing O.D. mm	T Threads	H1 Width across flats	H2 Width across flats	L1	L2	L3	M	Min. bore size	Effective area mm ²		Weight g
											Urethane tubing	Nylon tubing	
M5	KK2P-23E	ø3.2	M8 x 0.75	10	10	28.3	12.3	12.5	12.7	2.5	3.7	4.4	6.0
	-04E	ø4	M9 x 0.75	11	11	28.6		12.7	13.5	3.4	8.1	8.1	6.6
	-06E	ø6	M11 x 0.75	14	14	39.3		16.9	16.0	3.2	3.9	5.6	16.6
1/8	KK3P-04E	ø4	M12 x 1	17	17	40.2	18.4	16.8	17.0	4.7	10.1	12.8	22.3
	-06E	ø6	M14 x 1	19	19	43.4		20.0	18.5	6.0	15.7	22.6	30.2
	-08E	ø8	M16 x 1	22	24	46.4		22.0	21.0		22.6		54.7
	-10E	ø10	M20 x 1	22	24	46.4		22.0	21.0	7.7	27.6	35.3	61.4
1/4	KK4P-06E	ø6	M14 x 1	17	17	47.0	25.2	20.0	18.5	6.2	19.8	22.6	38.2
	-08E	ø8	M16 x 1	19	19	50.2		22.0	21.0	7.7	27.6	35.3	61.4
	-10E	ø10	M20 x 1	22	24	53.2		23.0	22.0	9.0	40.2	50.9	75.2
	-12E	ø12	M22 x 1	24	27	60.1		24.5	25.0	13.0	—		125.0
1/2	KK6P-12E	ø12	M22 x 1	24	27	60.1	31.0	23.0	22.0	9.2	41.2	50.9	86.1
	-16E	ø16	M28 x 1.5	30	32	62.6		24.5	25.0	13.0	—	106.2	125.0



Straight type with One-touch fitting

(mm)



KK2



KK3/4/6



Body size	Model	Applicable tubing O.D. mm	øD1	øD2	L1	L2 When connected	M	Min. bore size	Effective area mm ²		Weight g
									Urethane tubing	Nylon tubing	
M5	KK2S-23H	ø3.2	10.0	7.0	33.8	35.3	12.7	2.5	3.8	4.6	6.4
	-04H	ø4		8.0	33.6	35.1		3.4	4.0	4.8	6.5
	-06H	ø6		10.0	33.9	35.4		4.7	5.8	5.8	7.9
1/8	KK3S-04H	ø4	18.2	10.0	46.6	49.1	16.0	3.2	3.8	5.8	21.3
	-06H	ø6		12.0	47.1	49.6	17.0	4.7	10.4	13.4	23.2
	-08H	ø8		14.0	48.9	51.4	18.5	6.2	16.8	18.9	26.1
	-10H	ø10		17.0	49.9	52.4	21.0	7.7	19.1	19.1	35.9
1/4	KK4S-06H	ø6	25.4	12.0	58.2	61.9	17.0	4.7	10.4	13.4	48.6
	-08H	ø8		14.0	60.1	63.8	18.5	6.2	18.3	21.8	48.5
	-10H	ø10		17.0	61.5	65.2	21.0	7.7	27.0	29.4	52.0
	-12H	ø12		19.0	62.5	66.2	22.0	9.2	30.5	32.0	56.6
1/2	KK6S-12H	ø12	31.2	20.0	70.1	75.4	25.0	13.2	42.7	48.8	81.7
	-16H	ø16		25.7	72.3	77.6			53.4	62.5	97.5



Elbow type with One-touch fitting

(mm)



KK2



KK3/4/6



Body size	Model	Applicable tubing O.D. mm	øD1	øD2	L1	L2 When connected	L3	M	Min. bore size	Effective area mm ²		Weight g
										Urethane tubing	Nylon tubing	
M5	KK2S-23L	ø3.2	10.0	9.3	26.0	27.5	16.5	12.7	2.5	3.7	4.4	6.7
	-04L	ø4		11.6	27.2	28.3	16.6	13.5	4.5	5.6	5.6	7.2
	-06L	ø6		10.4	41.7	44.2	18.0	16.0	3.0	3.7	5.3	22.0
1/8	KK3S-04L	ø4	18.2	12.8	42.9	45.4	20.0	17.0	4.5	10.1	11.4	22.8
	-06L	ø6		15.2	43.1	45.6	23.0	18.5	6.0	15.0	16.8	23.8
	-08L	ø8		18.5	42.9	45.4	26.5	21.0	7.5	18.0	18.5	33.2
	-10L	ø10		12.8	54.3	58.0	20.0	17.0	4.5	10.1	11.4	50.7
1/4	KK4S-06L	ø6	25.4	15.2	55.5	59.2	23.0	18.5	6.0	17.5	19.8	50.3
	-08L	ø8		18.5	54.2	57.9	26.5	21.0	7.5	24.7	27.5	51.9
	-10L	ø10		20.9	55.4	59.1	28.5	22.0	9.0	29.0	29.6	54.2
	-12L	ø12		26.5	66.3	71.6	34.0	25.0	13.0	38.1	39.7	89.0
1/2	KK6S-12L	ø12	31.2	26.5	66.9	72.2	34.0	25.0	13.0	50.3	58.7	91.1
	-16L	ø16										



Bulkhead type with One-touch fitting

(mm)



KK2



KK3/4/6



Body size	Model	Applicable tubing O.D. mm	T Threads	H1 Width across flats	H2 Width across flats	øD	L1	L2 When connected	L3	M	Min. bore size	Effective area mm ²		Weight g
												Urethane tubing	Nylon tubing	
M5	KK2S-23E	ø3.2	M8 x 0.75	10	10	10.0	33.8	35.3	13.0	12.7	2.5	3.8	4.6	9.6
	-04E	ø4	M9 x 0.75	11	11		33.5	35.0	13.0	12.7	3.4	4.0	4.8	9.1
	-06E	ø6	M11 x 0.75	14	14		33.9	35.4	13.1	13.5	4.7	5.8	5.8	12.6
1/8	KK3S-04E	ø4	M12 x 1	14	14	18.2	46.6	49.1	16.9	16.0	3.2	3.8	5.8	27.8
	-06E	ø6	M14 x 1	17	17		47.1	49.6	16.8	17.0	4.7	10.4	13.4	38.2
	-08E	ø8	M16 x 1	19	19		49.0	51.5	20.0	18.5	6.2	16.8	18.9	42.2
	-10E	ø10	M20 x 1	22	24		49.9	52.4	22.0	21.0	7.7	19.1	19.1	67.1
1/4	KK4S-06E	ø6	M14 x 1	19	17	25.4	58.2	61.9	16.8	17.0	4.7	10.4	13.4	54.4
	-08E	ø8	M16 x 1	19	19		60.1	63.8	20.0	18.5	6.2	18.3	21.8	57.8
	-10E	ø10	M20 x 1	22	24		61.7	65.4	22.0	21.0	7.7	27.0	29.4	84.0
	-12E	ø12	M22 x 1	24	27		62.7	66.4	23.0	22.0	9.2	30.5	32.0	102.9
1/2	KK6S-12E	ø12	M22 x 1	24	27	31.2	70.1	75.4	24.5	25.0	13.2	42.7	48.8	113.6
	-16E	ø16	M28 x 1.5	30	32		72.5	77.8				53.4	62.5	180.8




S Couplers

Series KKH



With shock absorption cover

- Able to absorb drop impact (equivalent to impact energy of 0.5 J).



Sleeve cover ●
(Rubber)

- Same effective sectional area as that of Series KK.

Plug (P)

Male thread type

	Body size	Connection port size	Part no.
	1/8	R 1/8	KK3P-01MS
		R 1/4	-02MS
		R 3/8	-03MS
	1/4	R 1/8	KK4P-01MS
		R 1/4	-02MS
		R 3/8	-03MS
		R 1/2	-04MS

Female thread type

	Body size	Connection port size	Part no.
	1/8	Rc 1/8	KK3P-01F
		Rc 1/4	-02F
		Rc 3/8	-03F
	1/4	Rc 1/4	KK4P-02F
		Rc 3/8	-03F

Nut fitting type (for fiber reinforced urethane hose)

	Body size	Applicable hose I.D./O.D. mm	Part no.
	1/8	5/8	KK3P-50N
		6/9	-60N
		6.5/10	-65N
	1/4	5/8	KK4P-50N
		6/9	-60N
		6.5/10	-65N
		8/12	-80N
		8.5/12.5	-85N

Socket (S)

Male thread type

	Body size	Connection port size	Part no.
	1/8	R 1/8	KKH3S-01MS
		R 1/4	-02MS
		R 3/8	-03MS
	1/4	R 1/8	KKH4S-01MS
		R 1/4	-02MS
		R 3/8	-03MS
		R 1/2	-04MS

Female thread type

	Body size	Connection port size	Part no.
	1/8	Rc 1/8	KKH3S-01F
		Rc 1/4	-02F
		Rc 3/8	-03F
	1/4	Rc 1/4	KKH4S-02F
		Rc 3/8	-03F

Nut fitting type (for fiber reinforced urethane hose)

	Body size	Applicable hose I.D./O.D. mm	Part no.
	1/8	5/8	KKH3S-50N
		6/9	-60N
		6.5/10	-65N
	1/4	5/8	KKH4S-50N
		6/9	-60N
		6.5/10	-65N
		8/12	-80N
		8.5/12.5	-85N

Series KKH are only available as sockets.
Series KK should be used as plugs.

S Couplers Series *KKH*

With shock absorption cover




Specifications

Fluid	Air, Water (standard industrial water)
Operating pressure range ^{Note)}	KKH3: -90kPa to 1.0MPa KKH4: 0 to 1.0MPa
Proof pressure	1.5MPa
Ambient and fluid temperature	Air: -5 to 60°C Water: 5 to 40°C (with no freezing)
Plating, Sealant	Electroless nickel plated (copper-free application), With male thread sealant
Connection plug	Series KK plug

Note) Do not use the S couplers with a leak tester or for vacuum retention because they are not guaranteed for zero leakage.

JIS symbols



Performance


Plug and socket connection	One-touch connection and release
Check valve	Socket: Built-in check valve (standard)
Sleeve lock mechanism	—

Effective Area

Body size	Plug	Socket	Effective area mm ²
1/8	KK3P-01MS	KKH3S-01MS	20
1/4	KK4P-02MS	KKH4S-02MS	39

The flow characteristics are the same as those of Series KK.
Please refer to page 5.

How to Order



Series KKH


Dimensions/Socket (S)

Male thread type

(mm)



Body size	Model	T Connection port size	H Width across flats	øD	L1	L2 When connected	A1*	A2* When connected	Min. bore size	Effective area mm²	Weight g	
1/8	KKH3S-01MS	R 1/8	14	19.6	37.5	40.0	33.5	36.0	6.0	20.4	20.4	
	-02MS	R 1/4							31.5	34.0	9.0	21.1
	-03MS	R 3/8	17		38.7	41.0	32.2	34.5	9.0	27.8		
1/4	KKH4S-01MS	R 1/8	19	27.3	50.4	54.1	46.4	50.1	6.0	22.9	48.8	
	-02MS	R 1/4			51.0	54.7	45.0	48.7	9.0	38.9	45.4	
	-03MS	R 3/8	22		50.0	53.7	43.5	47.2	11.0	40.4	52.2	
	-04MS	R 1/2			49.7	53.4	41.7	45.4	13.0	42.7	62.5	




* Reference dimension for R threads after installation.

Female thread type

(mm)



Body size	Model	T Connection port size	H Width across flats	øD	L1	L2 When connected	Min. bore size	Effective area mm ²	Weight g
1/8	KKH3S-01F	Rc 1/8	14	19.6	36.0	38.5	8.2	20.6	23.9
	-02F	Rc 1/4	17		40.1	42.4		21.1	33.2
	-03F	Rc 3/8	19		41.9	44.3		37.2	
1/4	KKH4S-02F	Rc 1/4	19	27.3	50.4	54.1	10.9	39.6	58.2
	-03F	Rc 3/8			51.1	54.8	14.4	42.7	47.5




Nut fitting type (for fiber reinforced urethane hose)


(mm)




Body size	Model	Applicable hose I.D./O.D. mm	H1 Width across flats	H2 Width across flats	øD	L1	L2 When connected	M	Min. bore size	Effective area mm²	Weight g
1/8	KKH3S-50N	5/8	14	14	19.6	42.6	45.1	13.7	4.5	12.2	32.4
	-60N	6/9	17	17		44.4	46.9	16.5	5.4	18.3	49.0
	-65N	6.5/10							5.9	19.2	46.7
1/4	KKH4S-50N	5/8	19	14	27.3				54.1	57.8	13.7
	-60N	6/9		17		56.8	60.5	16.5	5.4	20.4	70.6
	-65N	6.5/10							5.9	24.1	68.1
	-80N	8/12		19		55.4	59.1	17.4	7.4	35.1	69.8
	-85N	8.5/12.5							7.8	36.6	72.4



Series KKH are only available as sockets. Series KK should be used as plugs. For dimensions, please refer to page 7.



- **Body material: Stainless steel (SUS304)**
Seal material: Fluoro rubber (FKM)
- **Both plug and socket have an integral check valve.**
Available with and without check valves depending on the operating conditions.
- **Reduces liquid dripping when the plug and socket are uncoupled.**
Liquid dripping: 0.02 to 0.06 cm³ at each removal
Aeration: 0.1 to 0.2 cm³ at each removal



- **Non-greased specification (standard)**
O-ring: Fluorine coated
Sliding parts of plug and socket: Plated with fluorine-contained material
Allows smooth installation and removal even without grease
- **Fluid: Water, Air**
- **Operating temperature range: -5 to 100°C**
Note) Do not use S couplers with steam.

Series KKA

Plug (P)

With check valve

Male thread type

	Body size	Port size	Part no.
	1/8	R 1/8	KKA3P-01M
		R 1/4	-02M
		R 3/8	-03M
	1/4	R 1/4	KKA4P-02M
		R 3/8	-03M
		R 1/2	-04M
	1/2	R 3/8	KKA6P-03M
		R 1/2	-04M
		R 3/4	-06M

Female thread type

	Body size	Port size	Part no.
	1/8	Rc 1/8	KKA3P-01F
		Rc 1/4	-02F
		Rc 3/8	-03F
	1/4	Rc 1/4	KKA4P-02F
		Rc 3/8	-03F
		Rc 1/2	-04F
	1/2	Rc 3/8	KKA6P-03F
		Rc 1/2	-04F
		Rc 3/4	-06F

Without check valve

Male thread type

	Body size	Port size	Part no.
	1/8	R 1/8	KKA3P-01M-1
		R 1/4	-02M-1
		R 3/8	-03M-1
	1/4	R 1/4	KKA4P-02M-1
		R 3/8	-03M-1
		R 1/2	-04M-1
	1/2	R 3/8	KKA6P-03M-1
		R 1/2	-04M-1
		R 3/4	-06M-1

Female thread type

	Body size	Port size	Part no.
	1/8	Rc 1/8	KKA3P-01F-1
		Rc 1/4	-02F-1
		Rc 3/8	-03F-1
	1/4	Rc 1/4	KKA4P-02F-1
		Rc 3/8	-03F-1
		Rc 1/2	-04F-1
	1/2	Rc 3/8	KKA6P-03F-1
		Rc 1/2	-04F-1
		Rc 3/4	-06F-1

Socket (S)

With check valve

Male thread type

	Body size	Port size	Part no.
	1/8	R 1/8	KKA3S-01M
		R 1/4	-02M
		R 3/8	-03M
	1/4	R 1/4	KKA4S-02M
		R 3/8	-03M
		R 1/2	-04M
	1/2	R 3/8	KKA6S-03M
		R 1/2	-04M
		R 3/4	-06M

Female thread type

	Body size	Port size	Part no.
	1/8	Rc 1/8	KKA3S-01F
		Rc 1/4	-02F
		Rc 3/8	-03F
	1/4	Rc 1/4	KKA4S-02F
		Rc 3/8	-03F
		Rc 1/2	-04F
	1/2	Rc 3/8	KKA6S-03F
		Rc 1/2	-04F
		Rc 3/4	-06F

Without check valve

Male thread type

	Body size	Port size	Part no.
	1/8	R 1/8	KKA3S-01M-1
		R 1/4	-02M-1
		R 3/8	-03M-1
	1/4	R 1/4	KKA4S-02M-1
		R 3/8	-03M-1
		R 1/2	-04M-1
	1/2	R 3/8	KKA6S-03M-1
		R 1/2	-04M-1
		R 3/4	-06M-1

Female thread type

	Body size	Port size	Part no.
	1/8	Rc 1/8	KKA3S-01F-1
		Rc 1/4	-02F-1
		Rc 3/8	-03F-1
	1/4	Rc 1/4	KKA4S-02F-1
		Rc 3/8	-03F-1
		Rc 1/2	-04F-1
	1/2	Rc 3/8	KKA6S-03F-1
		Rc 1/2	-04F-1
		Rc 3/4	-06F-1

S Couplers

Series KKA

Stainless steel type



Specifications

Fluid	Water, Air
Operating pressure range ^{Note)}	KKA3: -100kPa to 1.0MPa KKA4-6: 0 to 1MPa
Proof pressure	10MPa
Ambient and fluid temperature	-5 to 100°C (with no freezing) Note) Do not use with steam.
Non-greased specification	No grease is used. Rubber: Fluorine coated, (Metal sliding parts: Plated with fluorine-contained material)
Material	Metal part: SUS304, Rubber material: Fluoro rubber (FKM)
Seal	With male thread seal

Note) Do not use the S couplers with a leak tester or for vacuum retention because they are not guaranteed for zero leakage.

Performance

Plug and socket connection	One-touch connection and release
Check valve	Plug and socket are available with and without check valves.

Note) Series KKA cannot be connected with Series KK or Series KKH.

Characteristics with check valve on both sides

Body size	Liquid dripping cm ³ at each removal	Aeration cm ³ at each removal
KKA3	0.02	0.1
KKA4	0.04	0.1
KKA6	0.06	0.2

Liquid dripping:

Volume of water leakage at the time when the plug and socket are uncoupled.


Aeration:

Volume of external air entrained when the plug and socket are connected.

Effective area

Built-in check valve	Plug	Socket	Effective area mm ²
Plug: With check valve Socket: With check valve	KKA3P-01F	KKA3S-01F	16.2
	KKA4P-02F	KKA4S-02F	26.5
	KKA6P-04F	KKA6S-04F	56.4
Plug: Without check valve Socket: With check valve	KKA3P-01M-1	KKA3S-01M	19.0
	KKA4P-02M-1	KKA4S-02M	30.5
	KKA6P-04M-1	KKA6S-04M	59.5
Plug: Without check valve Socket: Without check valve	KKA3P-01M-1	KKA3S-01M-1	20.8
	KKA4P-02M-1	KKA4S-02M-1	38.9
	KKA6P-04M-1	KKA6S-04M-1	79.3

JIS symbol



How to Order

KKA 4 P-02 M-1

Body size

3	1/8
4	1/4
6	1/2

Socket/Plug designation

P	Plug
S	Socket

Port size

Symbol	Thread size
01	R, Rc 1/8
02	R, Rc 1/4
03	R, Rc 3/8
04	R, Rc 1/2
06	R, Rc 3/4

Built-in check valve

Nil	With check valve
1	Without check valve

Connection type

Symbol	Type
M	Mail thread (with seal)
F	Female thread

	Plug	Socket	Availability
Built-in check valve	Yes	Yes	○
	No	Yes	○
	No	No	○
	Yes	No	×


Note) A plug with check valve should be used in combination with a socket with check valve.

If a socket without check valve is used, the check valve of the plug will not open.

Flow Characteristics


Air (0 to 1 MPa)

Plug: With check valve Socket: With check valve




Water (0 to 0.4 MPa)


Plug: With check valve Socket: With check valve




Plug: Without check valve Socket: With check valve




Plug: Without check valve Socket: With check valve




Plug: Without check valve Socket: Without check valve




Plug: Without check valve Socket: Without check valve




Construction



Plug



Socket



Plug

No.	Description	Material	Note
1	Stem	Stainless steel	Plated with fluorine-contained material
2	Rear stem	Stainless steel	
3	Plug valve	Stainless steel	
4	Valve O-ring	FKM	Fluorine coated
5	Stem O-ring	FKM	Fluorine coated
6	Plug valve spring	Stainless steel	

Socket

No.	Description	Material	Note
1	Body	Stainless steel	Plated with fluorine-contained material
2	Rear body	Stainless steel	
3	Socket valve	Stainless steel	
4	Collar	Stainless steel	Plated with fluorine-contained material
5	Sleeve	Stainless steel	Plated with fluorine-contained material
6	Valve O-ring	FKM	Fluorine coated
7	Plug O-ring	FKM	Fluorine coated
8	Body O-ring	FKM	Fluorine coated
9	Collar seal	FKM	Fluorine coated
10	Collar spring	Stainless steel	
11	Sleeve spring	Stainless steel	
12	Steel ball	Stainless steel	
13	Stopper ring	Stainless steel	

Series KKA

Dimensions/Plug (P)


With check valve

Male thread type

(mm)



Body size	Model	T Connection port size	H Width across flats	L1	L2	A	Min. bore size	Effective area mm ²	Weight g
1/8	KKA3P-01M	R 1/8	14	35.4	16.0	31.4	6.1	16.5	15.4
	-02M	R 1/4		38.4		32.4		17.5	19.8
	-03M	R 3/8	17	39.4		32.9		17.5	32.9
1/4	KKA4P-02M	R 1/4	17	42.2	18.9	36.2	8.0	28.3	28.3
	-03M	R 3/8		43.2		36.7		29.4	36.6
	-04M	R 1/2	22	46.2		38.2		29.4	65.9
1/2	KKA6P-03M	R 3/8	24	47.1	20.4	40.6	11.0	58.0	60.3
	-04M	R 1/2		47.9		39.9		61.0	69.2
	-06M	R 3/4	30	49.9		40.4		61.0	119.0




Female thread type

(mm)



Body size	Model	T Connection port size	H Width across flats	L1	L2	Min. bore size	Effective area mm ²	Weight g
1/8	KKA3P-01F	Rc 1/8	14	36.0	16.0	6.1	16.5	20.2
	-02F	Rc 1/4	17	39.6			17.5	31.8
	-03F	Rc 3/8	19	40.4			17.5	35.8
1/4	KKA4P-02F	Rc 1/4	17	43.4	18.9	8.0	28.3	36.1
	-03F	Rc 3/8	19	44.4			29.4	40.2
	-04F	Rc 1/2	24	48.6			29.4	69.7
1/2	KKA6P-03F	Rc 3/8	24	48.7	20.4	11.0	58.0	84.1
	-04F	Rc 1/2		52.9			61.0	79.7
	-06F	Rc 3/4	30	54.6			61.0	123.8




Without check valve

Male thread type

(mm)



Body size	Model	T Connection port size	H Width across flats	L1	L2	A	Min. bore size	Effective area mm ²	Weight g
1/8	KKA3P-01M-1	R 1/8	12	28.5	16.0	24.5	6.0	20.7	9.8
	-02M-1	R 1/4	14	31.5		25.5		25.0	14.6
	-03M-1	R 3/8	17	32.5		26.0		25.0	23.6
1/4	KKA4P-02M-1	R 1/4	17	34.4	18.9	28.4	8.0	39.6	21.0
	-03M-1	R 3/8		35.4		28.9		41.9	27.9
	-04M-1	R 1/2	22	39.4		31.4		41.9	50.2
1/2	KKA6P-03M-1	R 3/8	22	37.9	20.4	31.4	11.0	71.8	41.9
	-04M-1	R 1/2		40.9		32.9		79.3	56.0
	-06M-1	R 3/4	30	42.9		33.4		79.3	98.7




Female thread type

(mm)



Body size	Model	T Connection port size	H Width across flats	L1	L2	Min. bore size	Effective area mm ²	Weight g
1/8	KKA3P-01F-1	Rc 1/8	14	23.2	16.0	6.0	20.9	9.6
	-02F-1	Rc 1/4	17	30.3			25.3	20.2
	-03F-1	Rc 3/8	19	32.0			25.3	26.2
1/4	KKA4P-02F-1	Rc 1/4	17	29.7	18.9	8.0	40.4	20.0
	-03F-1	Rc 3/8	19	34.0			42.7	25.8
	-04F-1	Rc 1/2	24	39.4			42.7	46.1
1/2	KKA6P-03F-1	Rc 3/8	22	30.9	20.4	11.0	73.2	34.3
	-04F-1	Rc 1/2	24	39.6			80.8	50.0
	-06F-1	Rc 3/4	30	42.8			80.8	78.6



Dimensions/Socket (S)


With check valve

Male thread type

(mm)



Body size	Model	T Connection port size	H Width across flats	øD	L	A	Min. bore size	Effective area mm²	Weight g
1/8	KKA3S-01M	R 1/8	17	18.5	38.1	34.1	6.1	18.8	38.5
	-02M	R 1/4			41.1	35.1		20.1	41.8
	-03M	R 3/8			42.1	35.6		20.1	46.3
1/4	KKA4S-02M	R 1/4	22	24.2	46.0	40.0	8.1	31.3	76.8
	-03M	R 3/8			47.0	40.5		32.8	78.5
	-04M	R 1/2			50.0	42.0		32.8	86.6
1/2	KKA6S-03M	R 3/8	30	30.7	51.4	44.9	11.0	58.0	149.1
	-04M	R 1/2			54.4	46.4	11.4	59.5	160.4
	-06M	R 3/4			56.4	46.9			184.8




Female thread type

(mm)



Body size	Model	T Connection port size	H Width across flats	øD	L	Min. bore size	Effective area mm²	Weight g
1/8	KKA3S-01F	Rc 1/8	17	18.5	37.6	6.1	18.8	46.9
	-02F	Rc 1/4			41.2		20.1	47.2
	-03F	Rc 3/8	19		43.1		20.1	52.3
1/4	KKA4S-02F	Rc 1/4	22	24.2	46.1	8.1	31.3	97.1
	-03F	Rc 3/8			46.9		32.8	91.1
	-04F	Rc 1/2	24		52.3		32.8	104.3
1/2	KKA6S-03F	Rc 3/8	30	30.7	50.5	11.4	58.0	189.6
	-04F	Rc 1/2			56.2		59.5	202.0
	-06F	Rc 3/4			57.9			180.6




Without check valve

Male thread type

(mm)



Body size	Model	T Connection port size	H Width across flats	øD	L	A	Min. bore size	Effective area mm²	Weight g
1/8	KKA3S-01M-1	R 1/8	17	18.5	38.1	34.1	6.1	21.7	36.1
	-02M-1	R 1/4			41.1	35.1		25.8	39.4
	-03M-1	R 3/8			42.1	35.6		25.8	43.9
1/4	KKA4S-02M-1	R 1/4	22	24.2	46.0	40.0	8.1	41.9	71.9
	-03M-1	R 3/8			47.0	40.5		44.2	73.6
	-04M-1	R 1/2			50.0	42.0		44.2	81.7
1/2	KKA6S-03M-1	R 3/8	30	30.7	51.4	44.9	11.0	79.3	138.3
	-04M-1	R 1/2			54.4	46.4	11.4	88.5	149.6
	-06M-1	R 3/4			56.4	46.9			174.0




Female thread type

(mm)



Body size	Model	T Connection port size	H Width across flats	øD	L	Min. bore size	Effective area mm²	Weight g
1/8	KKA3S-01F-1	Rc 1/8	17	18.5	37.6	6.1	21.7	44.5
	-02F-1	Rc 1/4			41.2		25.8	44.8
	-03F-1	Rc 3/8	19		43.1		25.8	49.9
1/4	KKA4S-02F-1	Rc 1/4	22	24.2	46.1	8.1	41.9	92.2
	-03F-1	Rc 3/8			46.9		44.2	86.2
	-04F-1	Rc 1/2	24		52.3		44.2	99.4
1/2	KKA6S-03F-1	Rc 3/8	30	30.7	50.5	11.4	79.3	178.8
	-04F-1	Rc 1/2			56.2		88.5	191.2
	-06F-1	Rc 3/4			57.9			169.8





S Couplers

Series KK13

Manufactured by Rectus




● One-touch connection

- Can be connected by simply pushing the plug into the socket.
- Manipulation with one hand improves work efficiency.

● Flow is possible from the plug side or socket side.

● O-ring seal construction for outstanding air tightness and durability.



Plug (P)

Male thread type

	Port size	Part no.
	R 1/8	KK13P-01M
	R 1/4	-02M
	R 3/8	-03M
	R 1/2	-04M

Female thread type

	Port size	Part no.
	Rc 1/4	KK13P-02F
	Rc 3/8	-03F
	Rc 1/2	-04F
	G1/4	-G02F

Barb fitting type

	Applicable hose I.D.	Part no.
	1/4"	KK13P-07B
	1/4"	-09B
	3/8"	-11B
	1/2"	-13B

Nut fitting type (for fiber reinforced urethane hose)

	Applicable hose I.D./O.D.	Part no.
	5/8	KK13P-50N
	6/9	-60N
	6.5/10	-65N
	8/12	-80N
	8.5/12.5	-85N
	11/16	-110N

Socket (S)

Male thread type

	Port size	Part no.
	R 1/8	KK13S-01M
	R 1/4	-02M
	R 3/8	-03M
	R 1/2	-04M

Female thread type

	Port size	Part no.
	Rc 1/4	KK13S-02F
	Rc 3/8	-03F
	Rc 1/2	-04F

Barb fitting type

	Applicable hose I.D.	Part no.
	1/4"	KK13S-07B
	1/4"	-09B
	3/8"	-11B
	1/2"	-13B

Nut fitting type (for fiber reinforced urethane hose)

	Applicable hose I.D./O.D.	Part no.
	5/8	KK13S-50N
	6/9	-60N
	6.5/10	-65N
	8/12	-80N
	8.5/12.5	-85N
	11/16	-110N

S Couplers

Series *KK13*

Manufactured by Rectus



Specifications

Fluid	Air (Note)
Operating pressure range	0 to 1.5MPa
Proof pressure	2MPa
Ambient and fluid temperature	–5 to 60°C
Plating	Nickel plated external metal parts

(Note) Cannot be used with water.


Performance

Plug and socket connection	One-touch connection and release
Check valve	Socket: Built-in check valve (standard)

Effective Area

Body size	Plug	Socket	Effective area mm ²
1/4	KK13P-02M	KK13S-02M	24.1
	KK13P-03M	KK13S-03M	31.1

JIS symbols



How to Order

KK 13 S-02 M

Series 13

Connection type

M	Male thread
F	Female thread
B	With barb fitting
N	With nut fitting

Socket/Plug designation

S	Socket
P	Plug

Port size variation

Male/Female thread type	
Symbol	Thread size
01	R, Rc 1/8
02	R, Rc 1/4
03	R, Rc 3/8
04	R, Rc 1/2
G02	G1/4

Barb fitting type


Symbol	Hose I.D.
07	6(1/4")
09	8(1/4")
11	9(3/8")
13	12(1/2")

Nut fitting type


Symbol	Applicable hose I.D./O.D.
50	5/8
60	6/9
65	6.5/10
80	8/12
85	8.5/12.5
110	11/16

Series KK13

Flow Characteristics



Construction



Plug

No.	Description	Material	Note
1	Stem	Steel	Nickel plated


Socket

No.	Description	Material	Note
1	Coupling body	Brass	Nickel plated
2	Plug O-ring	NBR	
3	Body	Brass	Nickel plated
4	Sleeve	Brass	Nickel plated
5	Snap ring	Stainless steel	
6	Collar	Brass	
7	Sleeve spring	Stainless steel	
8	Locking pin	Stainless steel	
9	Valve spring	Stainless steel	
10	Valve O-ring	NBR	
11	Valve	Brass	

Dimensions

Plug (P)


Male thread type



Model	T Connection male threads	H Width across flats	L ₁	A*	Min. bore size	Effective area mm ²	Weight g
KK13P-01M	R1/8	14	34.0	30.0	6.0	22.6	18
-02M	R1/4		37.0	31.0			22
-03M	R3/8	17		30.6	7.5	35.3	27
-04M	R1/2	22	44.0	35.8			51


* Reference dimension after installation.

Female thread type



Model	T Connection female threads	H Width across flats	L ₁	Min. bore size	Effective area mm ²	Weight g
KK13P-02F	Rc 1/4	17	35.5			27
-03F	Rc 3/8	19	39.0	7.5	35.3	32
-04F	Rc 1/4	24	42.5			51
-G02F	G1/4	17	32.0			27

Barb fitting type (for rubber hose)




Model	Hose I.D.	øD	Min. bore size	Effective area mm ²	Weight g
KK13P-07B	6(1/4")	7.5	4.1	10.6	17
-09B	8(1/4")	9.4	6.0	22.6	18
-11B	9(3/8")	11.5	7.5	35.3	21
-13B	12(1/2")	14.5			25

Refer to page 9 for calculation of the connected plug and socket dimension.

Socket (S)


Male thread type



Model	T Connection male threads	L ₁	A*	Min. bore size	Effective area mm ²	Weight g
KK13S-01M	R 1/8	45.5	41.5	6.0	19.0	81
-02M	R 1/4	48.5	42.5	7.0	24.1	86
-03M	R 3/8		42.1	10.2	31.1	89
-04M	R 1/2	53.0	44.8		32.1	108


* Reference dimension after installation.

Female thread type



Model	T Connection female threads	H Width across flats	L ₁	Min. bore size	Effective area mm ²	Weight g
KK13S-02F	Rc 1/4	22	47.0	10.5	25.7	103
-03F	Rc 3/8		52.0	10.2	31.1	107
-04F	Rc 1/2	24	55.5		32.1	117

Barb fitting type (for rubber hose)




Model	Hose I.D.	øD	Min. bore size	Effective area mm ²	Weight g
KK13S-07B	6(1/4")	7.5	4.1	8.0	81
-09B	8(1/4")	9.5	6.0	16.1	83
-11B	9(3/8")	11.5	8.0	25.4	
-13B	12(1/2")	14.5	10.2	31.9	88

Dimensions

Plug (P)


Nut fitting type (for fiber reinforced urethane hose)



(mm)							
Model	Applicable hose I.D./O.D.	H1 Width across flats	H2 Width across flats	L1	M	Effective area mm ²	Weight g
KK13P-50N	5/8					10.6	
-60N	6/9	17	17	43.0	17.0	16.3	42
-65N	6.5/10						
-80N	8/12						
-85N	8.5/12.5	19	19	45.0	19.0	28.5	52
-110N	11/16	23	23	52.0	23.0	30.9	98

Socket (S)

Nut fitting type (for fiber reinforced urethane hose)



(mm)							
Model	Applicable hose I.D./O.D.	H1 Width across flats	H2 Width across flats	L1	M	Effective area mm ²	Weight g
KK13S-50N	5/8					8.5	
-60N	6/9		17	53.2	17.0	14.0	98
-65N	6.5/10	21					
-80N	8/12		19	55.2	19.0	22.9	105
-85N	8.5/12.5						
-110N	11/16	24	23	59.2	23.0	25.0	142



Series *KK/KK13*

Safety Instructions

These safety instructions are intended to prevent a hazardous situation and/or equipment damage. These instructions indicate the level of potential hazard by a label of "**Caution**", "**Warning**" or "**Danger**". To ensure safety, be sure to observe ISO 4414 Note 1), JIS B 8370 Note 2) and other safety practices.

 **Caution** : Operator error could result in injury or equipment damage.

 **Warning** : Operator error could result in serious injury or loss of life.

 **Danger** : In extreme conditions, there is a possible result of serious injury or loss of life.

Note 1) ISO 4414: Pneumatic fluid power – General rules relating to systems.

Note 2) JIS B 8370: General Rules for Pneumatic Equipment

Warning

1. The compatibility of pneumatic equipment is the responsibility of the person who designs the pneumatic system or decides its specifications.

Since the products specified here are used in various operating conditions, their compatibility for the specific pneumatic system must be based on specifications or after analysis and/or tests to meet your specific requirements.

2. Only trained personnel should operate pneumatically operated machinery and equipment.

Compressed air can be dangerous if handled incorrectly. Assembly, handling or repair of pneumatic systems should be performed by trained and experienced operators.

3. Do not service machinery/equipment or attempt to remove components until safety is confirmed.

1. Inspection and maintenance of machinery/equipment should only be performed after confirmation of safe locked-out control positions.
2. When equipment is to be removed, confirm the safety process as mentioned above. Cut the supply pressure for this equipment and exhaust all residual compressed air in the system.
3. Before machinery/equipment is restarted, take measures to prevent shooting-out of cylinder piston rod, etc. (Bleed air into the system gradually to create back pressure.)

4. Contact SMC if the product is to be used in any of the following conditions:

1. Conditions and environments beyond the given specifications, or if product is used outdoors.
2. Installation on equipment in conjunction with atomic energy, railway, air navigation, vehicles, medical equipment, food and beverages, recreation equipment, emergency stop circuits, press applications, or safety equipment.
3. An application which has the possibility of having negative effects on people, property, or animals, requiring special safety analysis.



S Couplers Common Precautions 1

Be sure to read before handling.

Selection

Warning

1. Cannot be used as a stop valve that requires zero leakage. A certain amount of leakage is allowed during operation.
2. Series KK and Series KKH cannot be connected with Series KKA. Also, SMC's S coupler cannot be connected with quick couplers of other brands.
This will cause leakage, damage, and disconnection of the plug.
With series KK13, manufactured by Rectus, verify the manufacturer of applicable couplers before use.
3. Do not couple or uncouple the S coupler during pressurization or while residual pressure remains. The coupler may shoot out under the influence of the pressure.
4. Never apply pressure to an S coupler without check valve when it is uncoupled. The piping may move violently and cause danger.
5. An S coupler without check valve experiences leakage of fluid inside piping when it is uncoupled. Pay special attention in using fluid that can cause danger such as fluid of a high temperature and pressure. Additional use of a stop valve is recommended.
6. The S coupler is heated when used at a high temperature. Take precautions not to touch it since touching it can cause burns.

Caution

1. For a plug and socket connection, select a plug and socket with the same body size. If their body sizes are different, they cannot be connected. This will cause leakage, damage, and disconnection of the plug.
2. Do not use in locations where the connecting threads and tubing connection will slide or rotate. The connecting threads and tubing connection will come apart under these conditions.
3. Use tubing at or above the minimum bending radius. Using below the minimum bending radius can cause breakage or flattening of the tube.
4. Do not use couplers with flammable, explosive, or toxic substances, such as gas, gas fuel, and refrigerant. They may leak from inside the tubing to the outside.
5. Can be used with standard industrial water. When using with other liquids, consult SMC.
Also, operate with a surge pressure of no more than the maximum operating pressure. If the surge pressure exceeds the maximum operating pressure, it will cause damage to couplers and tubing.
6. Do not use the S coupler with steam. Corrosion of the metal material and deterioration of the sealing material may result from long-term use with steam.

Mounting

Warning

1. Do not use couplers where rotation normally occurs. The couplers may be damaged.
2. Avoid applications in which vibration or shock is directly applied to the fittings.
3. Fittings with sleeve lock mechanism must be locked during operation in order to prevent sudden disconnection.
4. Install a stop valve at the supply pressure side of the socket. Emergency shutdown may not be possible without it.

Caution

1. Before mounting confirm the model and size, etc. Also, confirm that there are no blemishes, nicks or cracks in the product.
2. When connecting a tube, consider factors such as changes in the tubing length due to pressure, and allow sufficient leeway.
3. Mount so that couplers and tubing are not subjected to twisting, pulling or moment loads. This can cause damage to couplers and flattening, bursting or disconnection of tubing, etc.
4. Mount so that tubing is not damaged due to tangling and abrasion. This can cause flattening, bursting or disconnection of tubing, etc.

Operating Environment

Warning

1. Do not use in locations where static electric charges will be a problem. Consult SMC regarding use in this kind of environment.
2. Do not use in locations where spatter occurs.
There is a danger of spatter causing a fire. Consult SMC regarding use in this kind of environment.
3. Do not use in environments where there is direct contact with liquids such as cutting oil, lubricating oil or coolant oil, etc. Contact SMC regarding use in environments where there will be direct contact with cutting oil, lubricating oil or coolant oil, etc.

Maintenance

Caution

1. Check for the following during regular maintenance, and replace components as necessary.
 - a) Scratches, gouges, abrasion, corrosion
 - b) Leakage
 - c) Twisting, flattening or distortion of tubing
 - d) Hardening, deterioration or softness of tubing
2. Do not repair or patch the replaced tubing or couplers for reuse.
3. Do not disassemble the S coupler. Spare parts are not available for this product.



S Couplers Common Precautions 2

Be sure to read before handling.


Handling

⚠ Warning


1. When connecting the plug, hold the plug securely. The plug may be uncoupled due to reaction at the time of connection.
2. When removing the plug, hold the plug securely. The tube may move due to reaction at the time of removal or the residual pressure inside the plug.

Plug Insertion Force in Pressurized Condition

Insertion force of Series KK



Insertion force of Series KKA



Handling of One-touch Fittings

⚠ Caution

1. Tube attachment/detachment for One-touch fittings
 - 1) Attaching of tubing
 1. Take a tube having no flaws on its periphery and cut it off at a right angle. When cutting the tubing, use tubing cutters TK-1, 2 or 3. Do not use pinchers, nippers or scissors, etc. If cutting is done with tools other than tubing cutters, the tubing may be cut diagonally or become flattened, etc. This can make a secure installation impossible, and cause problems such as the tubing pulling out after installation or air leakage. Allow some extra length in the tubing.
 2. Grasp the tubing and push it in slowly, inserting it securely all the way into the fitting.
 3. After inserting the tubing, pull on it lightly to confirm that it will not come out. If it is not installed securely all the way into the fitting, this can cause problems such as air leakage or the tubing pulling out.
 - 2) Detaching of tubing
 1. Push in the release bushing sufficiently. When doing this, push the collar evenly.
 2. Pull out the tubing while holding down the release bushing so that it does not come out. If the release bushing is not pressed down sufficiently, there will be increased bite on the tubing and it will become more difficult to pull it out.
 3. When the removed tubing is to be used again, cut off the portion which has been chewed before reusing it. If the chewed portion of the tubing is used as is, this can cause trouble such as air leakage or difficulty in removing the tubing.
2. When mounting a One-touch fitting, use a suitable wrench to tighten the hexagonal flats of the fitting. Moreover, position the wrench at the lower part of the hexagonal flats as close to the threads as possible. When a wrench of the proper size for the hexagonal flats is not used, it will cause the hexagonal flats to wear down.
3. Tightening of M3, M5, and M6 screws
 - 1) M3
After tightening by hand, tighten an additional 1/4 rotation with a tool.
 - 2) M5 and M6
After tightening by hand, tighten an additional 1/6 rotation with a tool.
- Over tightening can cause damage to the threads and/or air leakage due to deformation of the gasket. Under tightening can cause loose threads and air leakage, etc.



S Couplers

Common Precautions 3

Be sure to read before handling.

Handling of Barb Fittings and Nut Fittings

Caution

1. When using a nut fitting, insert the hose all the way to the end and securely tighten it with the nut. When the insertion of the hose or the tightening of the nut are not sufficient, the hose may slip out.
2. Disconnection may occur depending on the material or the O.D. accuracy of the hose; therefore be sure to confirm the applicability of the hose.

Handling of Fittings with Sealant

Caution

1. Tighten fittings with sealant using the proper tightening torques in the table below. As a rule, they should be tightened 2 to 3 turns with a tool after first tightening by hand.

Connection thread size	Proper tightening torque N·m
NPT 1/16, NPT, R1/8	7 to 9
NPT, R1/4	12 to 14
NPT, R3/8	22 to 24
NPT, R1/2	28 to 30

2. When a fitting is over tightened, more of the sealant material is squeezed out. Remove the squeezed out sealant material.
3. When tightening is not sufficient, it will cause sealant failure or a loose fitting.
4. Re-using
 - 1) Normally, a fitting with sealant can be re-used 2 to 3 times.
 - 2) Remove the sealant material that is separated and adhering to a removed fitting with air blow, etc. If the separated sealant enters into nearby equipment, it will cause air leakage or malfunction.
 - 3) When the sealant is no longer effective, wrap sealant tape over the sealant material and re-use the fitting. Do not use a sealant material other than sealant tape.
5. In cases where positioning is required, turning the fitting in the reverse direction after tightening will cause air leakage.

Precautions on Other Tubing Brands

Caution

1. When using tubing brands other than SMC, confirm that the tubing outside diameter tolerances satisfy the following specifications.
 - 1) Nylon tubing within $\pm 0.1\text{mm}$
 - 2) Soft nylon tubing within $\pm 0.1\text{mm}$
 - 3) Polyurethane tubing within $+0.15\text{mm}$
within -0.2mm

Do not use tubing if the outside diameter tolerance is not satisfied. It may not be possible to connect the tubing, or leakage or disconnection may occur after connection.



SMC CORPORATION

1-16-4 Shimbashi, Minato-ku, Tokyo 105-0004, JAPAN

Tel: 03-3502-2740 Fax: 03-3508-2480

URL <http://www.smcworld.com>

© 2002 SMC CORPORATION All Rights Reserved